# Semi-Automatic



## 2 C-ONE CRESCO



## Technical Data

Height 2238 mm
Width 1500 mm
Length 2375 mm
Turntable height 75 mm
Weight 260 kg
Power supply 230 VAC
Power absorption 1 kW

#### **C-One Cresco**

#### It is a small machine, but it can do a big job!


In creating Cresco, the C-One team looked at the essential points.

Cresco has only what it is really needed for a good wrapping machine: inverter for the turntable, inverter for the carriage, film stretching adjustment, pallet height sensor, bottom and top turns adjustment, zero position stop, three working cycles (up & down, only up, top-sheet), two working modes. 6 programs can be saved by the customer, including a completely customized cycle thanks to the "Playback" mode.

Even the structure is the result of a simplification process. Cresco is simply the core of what you need: a stretch wrapping machine. That's it!



## Semi-Automatic



## **Product Specifications**

- > Electronic printed circuit board for the management of the cycle
- > Frequency controller for turntable speed adjustment (from 3 to 12 RpM)
- > Frequency controller for carriage speed adjustment (speed going up and speed going down can be set differently)
- > Loading plate ø 1500 mm
- > Maximum wrapping height: 2200 mm
- > Maximum size of the pallet: 800x1200 mm
- > Maximum loading weight: 1200 kg
- > Electromagnetic brake for film stretching
- > Photocell for pallet height detection
- > Safety stop at the base of the carriage
- > Stop at 0 position
- > Power board IP54
- > 4 digits display
- > 2 access keys (including lock mode)
- > Adjustable parameters by the control panel: cycle selection, bottom turns, top turns, rotation speed, carriage speed going up, carriage speed going down, film tension.
- > Many parameters available at upper password level
- >Reinforcing operation
- > 3 working cycles: ascent/descent; topsheet; only ascent
- > 6 programs can be saved by the customer
- > "Playback" special cycle
- >2 working ways: semimanual, semiautomatic.
- > Acoustic warning at the cycle beginning and stop
- > Autodiagnostic
- > Powder coating
- > Braked turntable at the end of the cycle
- > 2 years warranty



EB Carriage

### **Main Options**

1650 mm turntable 2000 kg max pallet weight 2500 mm wrapping height Ramp Pit frame Photocell for dark loads Power pre-stretch carriage Power Pre-Stretch Carriage





Via Calcinaro N.2071 - 47521 Cesena (FC) Italy T. +39 (0)547 32 47 47 F. ++39 (0)547 32 47 66 | info@c-one.it | www.c-one.it





